

VUTEK PUSH CAMERA

VERSATILE SEWER INSPECTION CAMERA



PRODUCT OVERVIEW

The Vutek 2017 system has fully-loaded features to assist users with sewer inspections. The user-friendly keypad has been redesigned with an easy "On Demand" recording and snapshot button to help speed up inspection time. Technicians can easily record vital inspection data and client information using the available on-screen text-writer and footage counter. Built with a 1.3" modular, self-leveling camera head that is geared to inspect sewer pipes from 3" up to 12" inch diameter and a built-in sonde which broadcasts a 512 Hz frequency which is locatable with a 512 Hz locator.



FEATURES AND BENEFITS

NEW MOBILE PHONE APP

Download Insight Vision App to an approved Android™ or Apple™ phone.



Wi-Fi Video Streaming App

View, record, snapshot and share inspection videos.



One-Touch Recording and Snapshot

Record and take pictures during an inspection.



Keypad and On-Screen Text Enable

Type in vital information to display and record on video.



Built-in Microphone and Speaker

Record voiceover video and play it back.



On-Screen Footage Counter

View the distance pushed and display on screen.



Built-in 512 Hz Frequency Sonde

Broadcast a 512hz signal to be locatable with a 512hz locator.



Included External Battery Power Back

Power up the system for up to 6 hours on a full charge.



QUICK CHANGE MODULAR CAMERA

- 1.3" Diameter Camera Head
- Quick Camera Head Repair
- Clear Resolution Video
- Clearview Gorilla Glass
- Durable Stainless Steel Body
- Self-Leveling Camera Head





VUTEK PUSH CAMERA

INCLUDED WITH THE CAMERA SYSTEM



REEL COVER



2" SKID



3" SKID



USB STICK



POWER PACK



CAR POWER CORD



SUN SHADE

SPECIFICATIONS

CONTROL SYSTEM



Case Dimensions:
Video Resolution:
Data Storage:
Keyboard:
Recording format:
Image Capture:
Text Generator:
Distance Counter:
Video Out:
Camera Test Port:
Controls:
Power Source:
LCD Size:
Weight:
Battery:

12"L x 10"W x 9"H
640 x 480
8GB USB stick * **Included with the system**
Full "QWERTY" style membrane
H.264
JPG
Yes
Displays on screen FT/M
Yes
Yes
One Touch Recording
12V 5Amp DC * **Included with the system**
8.4"
13 lbs.
External Lithium-ion * **Included with the system**

CAMERA HEAD



Self-Leveling:
Dimensions:
Camera Resolution:
Weight:
Light Ring:
Imager Sensitivity:
Image Size/ Type:
Construction:
LED Window:
Camera Window:

Yes
2" L x 1.3" Diameter
640 x 480
5.9 Ounces
12 LED
.025 Lux
1/4" CMOS
Stainless Steel Body
Polycarbonate
Gorilla Glass

PUSH ROD/ FRAME



Cable Length:
Pipe Size:
Cable Jacket:
Cable core:
Push Rod Dia.:
Dimensions:
Weight:
Sonde Frequency:
Protective Skids:

200-300-400ft. Available.
3" to 12"
Polypropylene jacket
Spiral Wound Fiberglass push rod
0.475" OD
30"L x 16-1/2"W x 32-1/2"H
62 lbs. (200 ft.)
512Hz
2" & 3" * **Included with the system**

MOBILE PHONE APP



Local Wi-Fi:
Operating System:
Controls:
File transfer:
Video Connection:
Image Format:

Stream Wireless Video (No Internet Needed)
Approved Android & ISO devices capable (Free Download) View, record, playback and snapshot
Upload to Email or YouTube
Video Stream Up to 100ft.
JPG